

APPENDIX A


ENGINEERING APPENDIX PLATES 11 TO 38


Jacksonville Harbor Navigation Study, Duval County, Florida


DRAFT
INTEGRATED GENERAL REEVALUATION
REPORT II AND SUPPLEMENTAL
ENVIRONMENTAL IMPACT STATEMENT













































































Y= 2,182,000

SURVEY NOTES:

- 1. REFER TO SURVEY NO. 12-107.
- 2. ELEVATIONS ARE IN FEET AND TENTHS AND REFER TO THE NOAA REPORTED MEAN LOWER LOW WATER (MLLW) TIDAL DATUM RELATIVE TO THE
- 3. TIDAL REDUCTIONS WERE OBTAINED USING REAL-TIME KINEMATIC (RTK) GPS AND REFERENCED TO MILW UTILIZING A HYPACK KINEMATIC TIDAL DATUM MODEL FILE NAME: JAXHBR-VDATUM-2010APRIL26.KTD.
- 4. ALL ELEVATIONS ARE BELOW THE CHART DATUM UNLESS PRECEDED BY A
- 5. PLANE COORDINATES ARE BASED ON THE TRANSVERSE MERCATOR PROJECTION FOR THE EAST ZONE OF FLORIDA AND REFERENCED TO THE NORTH AMERICAN DATUM OF 1983 (NAD 83).
- 6. THIS SURVEY WAS PERFORMED USING REAL-TIME KINEMATIC (RTK) GPS POSITIONING WITH THE FOLLOWING REFERENCE BASE LOCATION:

"STARK"(OPUS PID: BBBZ99)

TIDE STAFF LOCATED AT "STARK" (OPUS PID# BBBZ99)

VERTICAL MEASUREMENTS WERE MADE USING AN R2SONIC 2024 MULTI BEAM SYSTEM AT 240 kHz AND A ROSS SINGLE BEAM SOUNDER AT 28 KHz

SURVEY VESSEL

DATE OF SURVEY 11 APRIL 2012

FLORIDA

JAX ODMDS

- 7. THE INFORMATION DEPICTED ON THIS MAP REPRESENTS THE RESULTS OF SURVEYS MADE ON THE DATES INDICATED ABOVE AND CAN ONLY BE CONSIDERED AS INDICATING THE GENERAL CONDITIONS AT THAT TIME. THIS CHART IS SOLELY FOR THE DISTRIBUTION OF AVAILABLE DEPTHS AT THE TIME OF SURVEY.
- 8. SURVEY ACCURACY STANDARDS, QUALITY CONTROL, AND QUALITY ASSURANCE REQUIREMENTS WERE FOLLOWED DURING THIS SURVEY IN ACCORDANCE WITH USACE EM 1110-2-1003, HYDROGRAPHIC SURVEYING, 1

ODMDS BOUNDARY POINTS	PLANE COORDINATES	
	X	Υ
POINT A	558,632	2,190,467
POINT B	564,590	2,190,451
POINT C	564,575	2,184,390
POINT D	558,616	2,184,405
POINT A'	559,131	2,189,965
POINT B'	564,089	2,189,952
POINT C'	564,076	2,184,891
POINT D'	559,117	2,184,904

NOTE: THE MAXIMUM ODMDS RELEASE ZONE IS DEFINED BY COORDINATES LISTED FOR CONTROL POINTS A', B', C', AND D'.

- 1. THE LIMITS SHOWN HEREON ARE FOR THE EXISTING ODMDS WHICH IS APPROXIMATELY 1 SQUARE MILE. THE FUTURE EXPANDED ODMOS WILL MEASURE APPROXIMATELY 4 SQUARE MILES.
- 2. THE MAXIMUM PLACEMENT ELEVATION IN THE JACKSONVILLE ODMDS

GRAPHIC SCALE

PLATE

SITE

Sea Plot

37

